

Sample Stream Accessories



FLOW-2HT
 Flow Indicator
 3/4" NPTM
 Stainless fittings(304)
 Polysulfone (PSU)
 Body & Piston
 Viton O-ring
 10 GPM max
 230 psi max
 300°F max
 8 1/2" long
 Installs at any angle



FLOW-75-10A
 Flow Indicator
 3/4" NPTM
 PVC fittings
 Polysulfone body
 Viton O-ring
 10 GPM max
 75 psi @ 130°F
 120 psi @ 75°F
 7 1/2" long
 Installs vertically



FLOW RESTRICTORS
 3/4" PVC • 125 psi max
 OR-3-BE • 3 GPM • Brass
 OR-3-BEP • 3 GPM • PVC
 OR-5-BE • 5 GPM • Brass
 OR-5-BEP • 5 GPM • PVC
 OR-8-BE • 8 GPM • Brass
 OR-8-BEP • 8 GPM • PVC



Paddle Style Flow Switch
 FS-PT 1/2" MNPT
 paddle switch only
 FS-PT-P Paddle switch
 with 1" PVC tee with 3/4" reducers
 FS-PT-075 3/4" MNPT
 paddle switch only
 FS-PT-B-075 3/4" MNPT
 paddle switch with 3/4" brass tee
 FS-PT-S-075 3/4" MNPT
 paddle switch with 3/4" iron tee



BACK CHECK VALVE
 CKV-3/4PP ... 3/4" FNPT, poly
 CKV-3/4SS ... 3/4" FNPT,
 stainless steel
 CKV-1PP 1" FNPT, poly



INJ-1 INJECTION TEE
 Quick release
 3/4" PVC tee with
 1/2" FNPT collar
 (Pump injection
 fitting not included)




Y-TEE LINE STRAINER
Polypropylene/PVC fittings
Steel mesh filter
75 psi max
150°F max
YP-³/₄
YP-1



INLINE BASKET STRAINER

Steel mesh filter (20×20)

Model	A	B
BL- ³ / ₄ - BLK	3½"	5"
BL-1	5"	6"
BL-1-CL (Clear)	5"	6"



BL-1-TOOL
Poly wrench for easy
removal and tightening of
BL-1 strainer bowls