

Specialty Sensors with 4-20 mA Output

Toroidal Conductivity

Max Temp 122°F (50°C)
 Max Pressure 72 PSI (5 bar)
 Body..... PP/PVC
 Power Supply..... 12-24 VDC
 Optional CPVC tee..... 2" slip
 Cable Length..... 9.5 ft.

TRX-001 0-1,000 uS/cm
 TRX-010 0-10,000 uS/cm
 TRX-100 0-100,000 uS/cm



Conductivity & Temperature

Operational Temp 32°-122°F (0°-50°C)
 Max Pressure 100 PSI
 Body..... CPVC
 Sensor 4-pin (carbon)
 Power Supply..... 22-26 VDC
 Wiring 5-wire
 Process Connection.. 3/4" CPVC tee
 Cable Length..... 5 ft.

STA-720 10-100,000 uS/cm
 32-122°F (0°-50°C)



Differential pH

Max Temp 185°F (85°C)
 Max Pressure 100 PSI
 Body / Salt Bridge..... PPS
 Wet End PVDF/Ceramic/Viton
 Power Supply..... 24 VDC
 Wiring 2-wire loop
 Process Connection.. 1.5" MNPT (dual)
 with 1.5" FNPT tee
 Cable Length..... 20 ft.

SDA-7420PH..... 0-14 pH



pH & ORP

Operational Temp 40°-104°F (4°-45°C)
 Max Pressure 100 PSI
 Outer Body 304 SS
 Replaceable Sensor .. UPVC
 Power Supply..... 22-26 VDC
 Wiring 4-wire
 Process Connection.. 3/4" CPVC tee
 submersible

Cable Length..... 8 ft.
 STA-710SS..... 0-14 pH
 STA-711SS..... ±1,500 mV
 STA-712SS..... 0-14 pH & ±1,500 mV



Dissolved Oxygen

Operational Temp 32°-113°F (0°-45°C)
 Max Pressure 75 PSI
 Body..... CPVC
 Power Supply..... 22-26 VDC
 Wiring 4-wire
 Process Connection.. Submersible, 3/4"
 MNPT back, CPVC
 tee optional
 Cable Length..... 30 ft.

STA-773 0-20 mg/L or 0-200%



Dissolved Oxygen & Temperature

Temp Range 32°-113°F (0°-40°C)
 Max Pressure 75 PSI
 Body..... 304 SS
 Power Supply..... 22-26 VDC
 Wiring 5-wire
 Process Connection.. Submersible, 3/4" MNPT
 back, 3/4" CPVC tee
 also included
 Cable Length..... 30 ft.

STA-772T 0-20 mg/L, 0-200%
 or 0-500 mbarP02
 Temperature output
 is 32°-122°F (0°-50°C)



Pressure

Max Fluid Temp..... 167°F (75°C)
 Body..... 316 SS
 Diaphragm..... Ceramic
 O-Ring..... Neoprene
 Power Supply..... 8-28 VDC
 Wiring..... 2-wire loop
 Process Connection.. ¼" MNPT
 Cable Connector..... M12

*Cables sold separately

PTD-100 0-100 PSI
 PTD-200 0-200 PSI



Temperature

Max Pressure 1,000 PSI
 Outer Body..... 304 SS
 Thermowell..... 316 SS
 Power Supply..... 9-28 VDC
 Wiring..... 2-wire loop
 Process Connection.. ¼" MNPT
 Cable Length..... 10 ft.



TTD-200-10 0°-200°F (-17.78°-93.33°C)

Turbidity and Suspended Solids with Wiper

Max Temp 122°F (50°C)
 Max Pressure 45 PSI
 Body..... 316 SS
 Power Supply..... 24 VDC
 Light..... LED:
 <100 NTU warm white
 >100 NTU IR
 850nm absorbance (TSS)

Wiring..... 4-wire
 Process Connection.. Submersible,
 ¾" (back)
 Cable Length..... 33 ft.

LTA-632 0-1,000 NTU
 LTA-635 0-30,000mg/L



Turbidity Ultra-Low Inline

Max Temp 131°F (55°C)
 Max Pressure 100 PSI
 Body..... 304 SS
 Light..... Warm white LED
 EPA-180.1 Compliant
 Power Supply..... 24 VDC
 Wiring..... 4-wire
 Process Connection.. ¾" tee, CPVC tee
 Cable Length..... 8 ft.

LTA-739 0.00-40.00 NTU

Process Connection Options:
 Flow Cell to Drain A-50779
 1.5" PVC Inline Tee A-50780



Toroidal Conductivity

Max Temp 140°F (60°C)
 Max Pressure 50 PSI
 Body..... CPVC
 Power Supply..... 24 VDC
 Wiring..... 2-wire loop
 Process Connection.. 1.5" MNPT (dual)
 Cable Length..... 20 ft.

TCA-C3254A 0-10 mS
 TCA-C3254B 0-100 mS



Advantage Controls offers additional sensors:

- Corrosion
- Fluorometer
- Level
- Oxidizer (Cl₂, ClO₂, Br₂, O₃, SO₃)



Scan QR code to visit.

Get the Advantage



4700 Harold-Abitz Dr
 Muskogee, OK 74403
 800-743-7431 Phone
 888-686-6212 Fax
www.advantagecontrols.com